



KAYCEE MINI TIME TOTALIZERS FOR AC & DC

APPLICATION:

Designed for monitoring or operating times of all AC & DC powered machines and plants.

Operating hours are required for many reasons. To find out operating costs, to check maintenance intervals or monitor guarantee periods. The basic design can be adapted to any range of applications by using additional components.

 $Kaycee\ Mini\ Time\ Totalizers\ record\ hours\ and\ 1/100th\ of\ an\ hour\ without\ reset\ and\ are\ available\ in\ 7\ digits-99999.99\ Hrs.$

Mounting: Two Varieties - Flush Panel mounting

MTT7/HZ Flush Panel Mounting

Flush mounting models fit into a cut-out of 45x45 mm. The thickness of the installation panel can vary up to 10 mm. A Rachet clamp is fitted for easy installation. This model does not have terminal cover and it is suitable for switching cabinets.

	SPECIFICATIONS	DIMENSIONS
RAYCEE MITTHE	7 Digits (Hours & 1/100): MTT7/Hz (0 to 99999.99) Dimensions (H x W x D): 48 x 48 x 40mm Panel cut out: 45 x 45mm Weight: 60gms Supply Voltage: 110V or 220V AC at 50HZ Power Input: Approx 1 VA Operating Temp. Range: -20°C to 55°C	48 WAYCEE WA
KAYCEE D D D D D D D D D D D D D D D D D D	7 Digits (Hours & 1/100): MTT7/Hz (0 to 99999.99) Dimensions: Dia 59mm, 53mm Ig. (up to Terminal) Panel cut out: 45 x 45mm Weight: 60gms Supply Voltage:10V-60V AC/DC or 60V-140V AC/DC or 140V-250V AC/DC. Power Input: Approx 1 VA Operating Temp. Range: -20°C to 55°C	5 KANCEE 100000000 h 100 m 100



Manufactured by:

KAYCEE INDUSTRIES LIMITED

32, Ramjibhai Kamani Road, Ballard Estate, Mumbai -400 001

Tel.: 91-22-22613521 / 22 / 33.

Fax: 91-22-22616106

Email: sales@kayceeindustries.com Website: www.kayceeindustries.com





