



RELAY



MY - SERIES



LY - SERIES



MK - SERIES

MODEL		MY SERIES			LY SERIES			MK SERIES	
		MY-2	MY-3	MY-4	LY-2	LY-3	LY-4	MK2P-1	MK3P-1
EXTERNAL DIMENSION (MM)	L	27.6			27.6	27.6	27.6	34.7	
	W	21.5			21.5	31.5	41.5	34.7	
	H	34			36	36	36	52	
CONTACT FORM		2A2B	3A3B	4A4B	2A2B	3A3B	4A4B	2A2B	3A3B
CONTACT CAPACITY		28V DC		220V AC		28V DC		220V AC	
		5A		3A		15A10A		10A 5A	
COIL VOLTAGE	DC	6,12,24,36,110 V			6,12,24,36,48,110 V			6,12,24,36,48,60,110,220 V	
	AC	6,12,24,36,110,220 V			6,12,24,36,48,110,220 V			6,12,24,36,48,60,110,127,220,380 V	
CONTACT RESISTANCE		$\leq 50m \Omega$			$\leq 50m \Omega$			$\leq 50m \Omega$	
INSULATION RESISTANCE		$\geq 1000m \Omega$			$\geq 1000m \Omega$			$\geq 500m \Omega$	
DIELECTRIC STRENGTH		1000V AC 50/60 Hz			1500V AC 50/60 Hz			1500V AC 50/60 Hz	
SERVICE LIFE	MECHANICAL	10,000,000			10,000,000			10,000,000	
	ELECTRICAL	100,000			100,000			100,000	
TERMINAL		OUTLET AND PRINTED CIRCUIT BOARD			OUTLET AND PRINTED CIRCUIT BOARD			OUTLET SOLDER	